

- Minor Losses in valves and joints
- Elevation differences across farm
- Pump horsepower requirements
- Kilowatt “demand” by pump
- Crop irrigation water needs
- Application efficiency
- Seasonal hours of operation

Each of the above areas is calculated in the worksheet or is given an average value for systems that are working satisfactorily. For example, the pump efficiency is needed to calculate horsepower requirements. Farmers may not know the pump efficiency. A “desired” value of 70% is used in the worksheet. If a farmer’s pump is operating at much less than this efficiency, the difference will show up when he compares the worksheet answer to his power bill.

STEPS IN EVALUATING POTENTIAL IRRIGATION ENERGY REDUCTION

To illustrate, let’s determine the seasonal energy requirements of 400 irrigated acres, 260 acres of alfalfa and 140 acres of spring grain, in an area where:

- The normal annual precipitation is 10 inches (October - March, 6 inches and April - September, 4 inches).
- Seasonal alfalfa crop water use (evapotranspiration, ET) is 36 inches. (Table 1.)
- Seasonal spring grain ET is 20 inches.
- The pumping level in the well is 120 feet.
- Average sprinkler operating pressure is 50 psi.
- The hydraulic friction headloss, elevation difference and minor losses are 40 feet.
- The system was designed to meet a peak period ET rate of 0.30 inches per day at 68% irrigation application efficiency. (See Table 2.)

DETERMINE SYSTEM FLOWRATE AND SEASONAL OPERATING HOURS

The seasonal crop water requirement supplied by irrigation equals the crop water use (evapotranspiration) minus the sum of stored soil water from winter precipitation and effective summer rainfall. As a rule of thumb, about two-thirds of the winter precipitation and four-fifths of the summer rainfall can be used by the crop. The required irrigation water delivery to the field equals the irrigation requirements divided by the irrigation system application efficiency.

	<u>Example</u>	<u>Your Value</u>
Stored winter precipitation $0.67 \times 6" =$ [$0.67 \times (\text{Oct} - \text{March Precip})$]	4	_____
Effective summer rainfall $0.80 \times 4" =$ [$0.80 \times (\text{Apr} - \text{Sep Rain})$]	3.2"	_____
Total usable natural moisture = (deduct Aug. and Sep. for Grain, use 6.0" in this example)	7.2"	_____

Crop water use supplied by irrigation equals crop ET minus usable natural moisture.

		<u>Example</u>	<u>Your Value</u>
Alfalfa (ET = 36")	36 - 7.2 =	28.8"	_____
Spring Grain (ET = 20")	20 - 6.0 =	14.0"	_____

Table 1. Typical Monthly Alfalfa Water Use (Evapotranspiration) Estimates for Selected Utah Locations.

Location	Peak ET In Days*	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Season Total
----- Inches -----											
Beaver	.33		0.05	5.29	6.17	7.50	6.73	2.71			28.5
Blanding	.31		2.80	6.31	5.61	7.54	6.49	3.86	1.70		34.3
Castle Dale	.35		0.48	5.49	6.95	8.47	7.04	4.52	1.30		34.3
Cedar City	.32		1.79	6.66	6.13	7.39	7.23	4.19	0.99		34.4
Corinne	.34	0.19	2.89	5.33	7.78	7.12	6.46	4.70	2.43		36.9
Delta	.35		2.72	6.53	7.43	7.52	6.55	5.02	0.96		36.7
Duchesne	.30		1.20	6.56	6.19	7.21	6.43	3.79	1.93		33.3
Escalante	.31		2.87	7.66	6.27	6.87	7.35	3.90	1.79		36.7
Farmington	.32	0.27	3.19	5.44	7.08	6.78	5.66	3.73	1.95		34.1
Green River	.36		3.09	7.45	6.77	7.69	7.96	4.49	2.64		40.1
Heber	.29		0.13	5.07	6.52	7.58	5.58	4.27	0.33		29.5
Kanab	.33	0.66	4.03	7.03	7.19	7.01	6.64	4.65	2.33		39.6
Koosharem	.27			3.04	7.37	6.13	5.94	3.44			25.9
Logan	.30		2.25	5.92	5.65	6.61	6.60	3.90	0.43		31.4
Manti	.34		1.20	6.69	6.23	7.77	7.79	4.57	1.31		35.6
Milford	.34		0.85	6.61	6.57	7.45	6.55	5.00			33.1
Moab	.34	0.98	4.23	6.88	7.10	7.15	6.05	4.74	3.22		40.4
Pleasant Grove	.33		2.37	5.97	6.87	6.86	5.61	4.05	1.10		32.9
Richfield	.32		1.05	6.48	6.25	6.99	6.08	4.43	0.43		31.7
Roosevelt	.34		1.97	7.15	6.52	7.48	7.07	3.86	0.95		35.0
St. George	.39	2.47	4.65	7.24	8.14	8.27	7.26	5.45	3.21	0.38	47.1
Snowville	.34		0.54	5.67	7.76	7.84	7.54	3.38	1.04		32.8
Tooele	.32		2.76	5.90	7.60	6.83	6.11	4.28	1.34		34.8
Vernal	.33		1.62	6.63	6.15	8.14	6.85	3.84	2.53		35.8
Woodruff	.28			1.93	6.73	6.00	5.77	3.13			23.6

*Average daily crop water use for the 14-day peak water use period.

Adapted from: Consumptive Use of Irrigated Crops in Utah, UT. Ag. Exp. Stn. Res. Report No. 145. Reference 1 at end of this worksheet.

Table 2. Water Application Efficiencies (Ea) for Properly Designed Sprinkler Irrigation Systems.

Depth of water applied per irrigation (ac in/acre)	Peak Use, Inches Per Day		
	<u>0.20 or Less</u>	<u>0.20 - 0.30</u>	<u>0.30 or more</u>
<u>Average Wind Movement, 0-4 mph</u>			
1"	68%	65%	62%
2"	70	68	65
4"	75	70	65
6"	80	75	70
<u>Average Wind Movement, 4-10 mph</u>			
1"	65%	62%	60%
2"	68	65	62
4"	70	68	65
6"	75	70	68
<u>Average Wind Movement, 10-15 mph</u>			
1"	62%	60%	58%
2"	65	62	60
4"	68	65	62
6"	70	68	65

From Ames Irrigation Handbook

Field irrigation delivery requirement equals crop water use supplied by irrigation divided by application efficiency (Ea, %/100) expressed as acre-inches/acre (which is equivalent to inches).

Alfalfa	$28.8 \div 0.68 =$	42.4"	_____
Spring Grain	$14.0 \div 0.68 =$	20.6"	_____

Required field irrigation delivery volume in acre-feet equals acre-inches divided by 12.

		<u>Example</u>	<u>Your Value</u>
Alfalfa (260 acres)	Vol = $260 \times 42.4/12 =$	919 ac-ft	_____
Spring Grain(140 acres)	Vol = $140 \times 20.6 =$	240	_____
Total for farm		1159	_____

System Flowrate

Every pump and irrigation system has a flowrate capacity which is based on a design flowrate (q). This flowrate is calculated by dividing peak period (7 to 14 days) average daily crop water use by the expected application efficiency and by an adjustment for system off-time for maintenance or sprinkler moves, etc. The design flowrate (q) is typically expressed as gpm/acre.

$$q = \frac{452.5 \times \text{peak ET (inches/day)}}{Ea \times \text{daily operating hours}}$$

	<u>Example</u>	<u>Your Value</u>
$q = \frac{452.5 \times 0.30}{0.68 \times 23} =$	8.7 gpm/ac	_____

The corresponding pumping capacity (Q) is determined by multiplying q by the irrigated area (400 acres in the example).

$Q = 8.7 \times 400 =$	3480 gpm	_____
------------------------	----------	-------

Seasonal Hours

Seasonal operating hours (t) equals 5430 times field delivery (acre-feet) divided by system flowrate (Q, gpm).

$t = 5430 \times 1159/3480 =$	1808 hrs	_____
-------------------------------	----------	-------

CALCULATE TOTAL DYNAMIC HEAD

Pumping lift, sprinkler pressure, friction losses and elevation differences are all expressed in feet of head.

	<u>Example</u>	<u>Your Value</u>
1. Total pumping water lift	120 ft	_____
2. Column friction head. Column losses typically vary from 3 to 8 feet per 100 ft of column. We'll use a value of 4.5 feet per 100 ft length, and assume the bowls are set 40 feet bellow the pumping water level (160 = 120 + 40). $4.5 \times 160/100 =$	7.2 ft	_____
3. System operating pressure converted to feet of head (50 psi x 2.31) =	115.5 ft	_____

Your sprinkler pressure _____ x 2.31 ft. _____

3. Pipeline hydraulic friction head loss, _____ ft _____
 minor losses and elevation difference. _____ ft _____
 _____ ft _____

Subtotal 40 ft _____

Total dynamic head (120 + 7.2 + 115.5 + 40) = 282.7 ft _____

CALCULATE POWER REQUIREMENTS

Pump horsepower requirements include the water horsepower and the electrical horsepower.

Water horsepower (Whp)

Whp is determined by multiplying the pump flowrate (Q, gpm) by the total dynamic head (TDH ft) and dividing by 3960.

	<u>Example</u>	<u>Your Value</u>
Whp = 3480 x 282.7/3960 =	248.4 hp	_____

Electrical power (Ehp)

Ehp is electrical power needed to meet the Whp requirement. It is calculated by dividing Whp by the pumping plant (pump and motor) efficiency (Ep).

Ehp = 248.4/0.7 = 354.9 hp _____

NOTE: A desired Ep is 0.7 (70%) for systems that operate efficiently. If the final answer of the worksheet shows a big difference from your power bill, then tests should be run to determine actual pump efficiency.

CALCULATE KILOWATT DEMAND

	<u>Example</u>	<u>Your Value</u>
kW = (Ehp x .746) = 354.9 x .746 =	264.8 kW	_____

NOTE: Actual kW demand can be measured during pump operation as part of a pump test.

SEASONAL ENERGY USE

Estimated energy costs include demand, energy and often, service charges. The energy usage depends on the kW demand and number of hours operated. For this example we will assume an average cost of 0.06\$/kW-hr including demand, energy and service charge.

Seasonal kilowatt hours equal demand kW times pump hours.

	<u>Example</u>	<u>Your Value</u>
264.8 x 1808 =	478,758 kW-hr KWh	_____

The estimated seasonal bill equals kilowatt hours times energy cost per kW-hr.

478,758 x \$.06 =	\$28,725	\$_____
-------------------	----------	---------

Cost per ac-ft of pumped water equals energy cost divided by acre-feet.

\$28,725/1159 =	\$25 /ac-ft \$_____/ac-ft
-----------------	------------------------------

SUMMARY

This example illustrates the steps necessary to evaluate the potential for reducing irrigation energy consumption on a given farm. With minor adjustments, energy consumption can be decreased. For example, if sprinklers were changed to low pressure nozzles (30 psi) instead of the assumed 50 psi, then the pump head could be reduced by 46 feet ($46 = (50 - 30) * 2.31$). For our example this is equivalent to reducing the demand by 43 kW with a potential savings of \$4,591 per season.

Changes in the efficiencies of the pumping plant and irrigation system application could show significant cost differences. For example, a pumping plant with 65% (instead of 70% which we use) efficiency would indicate a 36,200 kW-hr increase in one season. Which, at \$0.06/kW-hr would reflect an increased billing of \$2,171.

If actual energy usage is lower than what was calculated, then the pumping and application efficiencies may be greater than what was assumed and/or actual crop water use may be less than the assumed value. If crop yields are lower than expected then, perhaps, a deficit irrigation situation exists.

Many factors influence irrigation system application efficiency. For sprinkler systems, these include pressure, nozzle size and spacing, wind, air temperature (day versus night), interval between irrigations and maintenance condition. In some cases, more energy savings may be realized by management changes than by pump repairs. Pumping less water (possibly at lower pressures) through improved irrigation procedures and pumping plant improvement will aid in decreasing our continuing energy needs.

REFERENCES

1. Hill, R.W. 1994. Consumptive Use of Irrigated Crops in Utah. Utah. Agr. Exp. Stn. Res. Rpt. #145. Utah State University, Logan, UT. This report is available on the Web at: <http://nrwrtl.nr.state.ut.us/manuals/consumpt/cfwea.htm>

ACKNOWLEDGMENTS

This worksheet was adapted from an earlier 1988 version (1988) of the same title prepared with support from the Utah Department of Agriculture (now the Ut. Dept. of Ag. and Food) and USU Cooperative Extension.

Robert W. Hill, Professor and Extension Irrigation Specialist,
Biological and Irrigation Engineering Department,
Utah State University, Logan, UT, 84322-4105.

Utah State University Extension is an affirmative action/equal employment opportunity employer and educational organization. We offer our programs to persons regardless of race, color, national origin, sex, religion, age or disability.

Issued in furtherance of Cooperative Extension work, Acts of May 8 and June 30, 1914, in cooperation with the U.S. Department of Agriculture, Robert L. Gilliland, Vice-President and Director, Cooperative Extension Service, Utah State University, Logan, Utah. (EP/05-99/DF)