


# Easy Hot Pad



## Supplies needed:

- 8 ½" Insul-Bright batting 8
- ½" cotton batting
- 9" fabric matching thread
- 1 small plastic ring
- Sewing machine
- Basic sewing supplies (see Basic sewing supplies)


## Diagram Key:




Batting



Insul-Bright



Right side





Wrong side

## Cutting instructions:

### Step #1

- Cut 1 - 8 1/2" Square of Insul-Bright TM batting





- Cut 1 - 8 1/2" Square of cotton batting
- Cut 2 - 9" Squares of Fabric



## Hot pad construction:



### Step #1

- Place Cotton batting square on wrong side of the fabric square. Place Insul-Bright™ on wrong side of the other fabric square.




**Step #2**


- Machine quilt both of the squares. One square with a straight stitching and the other with a curved free hand design keeping the fabric and batting flat.

**Step #3**


- Pin quilted squares right sides together

**Step #4**

- Stitch a 5/8" seam starting 2 inch from the edge. Backstitch at the beginning and sew to 5/8" from the edge of the fabric. Lower the needle in the down position and pivot the hot pad. Continue sewing a 5/8" seam around the hot pad pivoting at each corner. Leave a 4" opening and backstitch.

**Step #5**


- Clip corners of the hot pad to the stitching line but not through it. Press flat to set the seam.

**Step #6**

- Turn the square to the right side making sure the corners and sides are pulled completely out.
- Press


## Authors

*Susan Haws, USU Extension Agent, Uintah County;  
Debra Proctor, USU Extension Agent, Wasatch  
County; Ronda Olsen, USU Extension Agent, Uintah  
County*



### Step #7

- Tuck seam allowance in and pin closed. Top- stitch using the edge of the presser foot as a guide. Pivot at each corner and overlap 4 to 5 stitches.



### Step #8

- Hand stitch small plastic ring in on corner of hot pad.

