

# Easy Sewing Maker Projects



**Phone**

## Charging Holder

### Materials Needed:

- 2 fabrics (5 ½" x 13")
- Heavy fusible interfacing (5 ½" x 13")
- Large grommet (2 ½" diameter)
- Coordinating thread

### Directions:

1. Press fusible interfacing onto wrong side of inside (lining) fabric.




Place the two fabrics right sides together and pin to secure the two fabrics together.

2. Sew on each side of the fabrics using a ¼" seam and leaving a 3" opening on one side.



3. Clip corners to reduce bulk and turn right sides out. Use a point turner to poke out corners if necessary.



4. Press around edges so that it lays flat. Press the opening in ¼" on each side so that it is flush with the edge seam.

5. With the inside facing up, fold the bottom up 4" and secure both sides with pins.

6. Starting on one bottom corner, sew 1/8" from edge, backstitch, and continue sewing up side, to the corner and pivot, across the top and pivot and then down the other side and to the bottom corner and back stitch.

7. Last, add the grommet. Find the middle and approximately 1/4" from the top, trace the template onto the fabric. Cut out the circle. Then place the raised center of grommet in hole from the back side to the front side of holder. On top, position the other side of the grommet and press until it clicks together.



2. Place the two fabrics right sides together and pin to secure the two fabrics together.

3. Fold ribbon in half with D ring 2" from the top end and pin to the inside.


4. Sew on each side of the fabrics using a 1/4" seam and leaving a 3" opening on one side.



5. Clip corners to reduce bulk and turn right sides out. Use a point turner to poke out corners if necessary.

6. Press around edges so that it lays flat. Press the opening in 1/4" on each side so that it is flush with the edge seam.

7. Sew Velcro onto top inside flap and the bottom of the outside.



Velcro piece on back side end.

8. With the inside facing up, fold the bottom up 3" and secure both sides with pins.



Lanyard


## Wallet

### Materials Needed:

- 2 fabrics (3 1/4" x 9")
- Heavy fusible interfacing (3 1/4" x 9")
- Velcro (3/4" x 2")
- 1/2" D ring Ribbon (1 1/2" of 3/8" wide)
- Coordinating thread

### Directions:


1. Press fusible interfacing onto inside fabric.



9. Starting on one bottom corner, sew 1/8" from edge, backstitch, and continue sewing up side, to the corner and pivot, across the top and pivot and then down the other side and to the bottom corner and back stitch.



3. Press seam open.



4. Turn right sides out and center the seam.

5. Place the fabric so that the seam side is down.

6. Now, bring the folded edges in to the center seam.

7. Pin in place.

8. Next, sew the 2 short raw edges 1/4" and back stitch on each end.

9. Clip corners and turn right side out.



**Travel**

## Tissue Cover

### Materials Needed:

- Fabric - 5 3/4" x 14"
- Thread

### Directions:

1. Fold fabric in half right sides together, so that the short sides are together.

2. Sew 1/4" seam along the short side.

## Authors

**Tricia Mathis**, FCS/4-H Educator; **Susan Haws**, FCS/4-H Associate Professor

